

- 21  
32. A printer system according to claim <sup>20</sup>31 wherein the distance between the drive circuitry and the liquid passage is less than 10 microns.
- 22  
33. A printer system according to claim <sup>20</sup>31 wherein the distance between the drive circuitry and the liquid passage is less than 5 microns.
- 23  
34. A printer system according to claim <sup>20</sup>31 wherein the width of the liquid passage is greater than 10 microns and less than 28 microns.

24  
35. A printer system according to claim <sup>20</sup>31 wherein the droplet ejection actuators are thermal bend actuators.

25  
36. A printer system according to claim <sup>20</sup>31 wherein the droplet ejection actuators are gas bubble generating heater elements.

10

26  
37. A printer system according to claim <sup>25</sup>36 further including a plurality of nozzle chambers, each nozzle chamber corresponding to a respective nozzle; wherein, at least one the of the gas bubble generating heater elements are disposed in each of the nozzle chambers respectively; such that, a bubble forming liquid can be supplied to the nozzle chamber for thermal contact with at least one of the bubble generating heater elements so that a bubble of the bubble forming liquid generated by one of the heater elements causes a drop of the ejectable liquid to be ejected from the nozzle.

27  
38. A printer system according to claim <sup>26</sup>37 wherein the bubble forming liquid is the same as the ejected liquid.

20

28  
39. A printer system according to claim <sup>20</sup>31 wherein the printhead is a pagewidth printhead.

Rule  
126  
12/30/05